

# ZT6000

## COMMERCIAL



| MODEL NUMBER                  | 9996010                                                     | 9996011                                                     |
|-------------------------------|-------------------------------------------------------------|-------------------------------------------------------------|
| <b>ENGINE</b>                 |                                                             |                                                             |
| Model                         | Kaw FX801V                                                  | Kaw FX801V                                                  |
| Horsepower                    | 25.5 hp (19.0 kW)                                           | 25.5 hp (19.0 kW)                                           |
| Displacement                  | 52.0 cu. in. (852 cc)                                       | 52.0 cu. in. (852 cc)                                       |
| Fuel Capacity                 | 15 gal. (56.7 L)                                            | 15 gal. (56.7 L)                                            |
| Air Filter                    | Canister Air Filter                                         | Canister Air Filter                                         |
| <b>ELECTRICAL</b>             |                                                             |                                                             |
| Charging System               | 15 amp                                                      | 15 amp                                                      |
| Clutch                        | 225 lbf. (1000 N)                                           | 225 lbf. (1000 N)                                           |
| <b>DECK</b>                   |                                                             |                                                             |
| Mower Deck                    | AirFX Cutting System                                        | AirFX Cutting System                                        |
| Leading Edge                  | Adjustable, Front Lip Standard                              | Adjustable, Front Lip Standard                              |
| Width                         | 52.0 in. (1320 mm)                                          | 61.0 in. (1549 mm)                                          |
| Adjustable Anti-Scalp Rollers | 6                                                           | 6                                                           |
| Cutting Height                | 1.0-5.5 in. (25-139 mm)                                     | 1.0-5.5 in. (25-139 mm)                                     |
| Blade Tip Speed               | 18,586 fpm @ 3550 Engine rpm                                | 18,500 fpm @ 3550 Engine rpm                                |
| Discharge Chute               | Flexible Molded Polymer                                     | Flexible Molded Polymer                                     |
| <b>FRAME</b>                  |                                                             |                                                             |
| Front and Rear                | 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame | 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame |
| Machine Length                | 83.0 in. (2108 mm)                                          | 83.0 in. (2108 mm)                                          |
| Machine Weight (wet)          | 1371 lb. (621 kg)                                           | 1421 lb. (644 kg)                                           |
| <b>TRANSMISSION</b>           |                                                             |                                                             |
| Type                          | HG ZT-4400 Hydrostatic Transaxles                           | HG ZT-4400 Hydrostatic Transaxles                           |
| Pump Displacement             | 0.7 cu. in. (12 cc)                                         | 0.7 cu. in. (12 cc)                                         |
| Oil Capacity                  | 0.9 gal. (3.5 qt.) each                                     | 0.9 gal. (3.5 qt.) each                                     |
| Forward Speed                 | 12.0 mph (19.3 km/hr.)                                      | 12.0 mph (19.3 km/hr.)                                      |
| Reverse Speed                 | 4.0 mph (6.4 km/hr.)                                        | 4.0 mph (6.4 km/hr.)                                        |
| <b>WHEELS</b>                 |                                                             |                                                             |
| Drive Wheel Size              | 24 x 10.5-12                                                | 24 x 10.5-12                                                |
| Front Caster Wheel Size       | 13 x 6.5-6                                                  | 13 x 6.5-6                                                  |
| Caster Arm Attachment         | Bolt-On                                                     | Bolt-On                                                     |
| <b>SEAT</b>                   |                                                             |                                                             |
| Description                   | High Back, Full Mechanical Suspension Seat                  | High Back, Full Mechanical Suspension Seat                  |
| Fore-Aft Adjustment           | Seat Slide Lever                                            | Seat Slide Lever                                            |
| <b>WARRANTY</b>               | 3-year/2,000-hour Limited Warranty                          |                                                             |