

# ZT5000

## COMMERCIAL



| MODEL NUMBER                  | 9995001                                                        | 9995002                                                        |
|-------------------------------|----------------------------------------------------------------|----------------------------------------------------------------|
| <b>ENGINE</b>                 |                                                                |                                                                |
| Model                         | Kaw FX730V                                                     | Kaw FX730V                                                     |
| Horsepower                    | 23.5 hp (17.2 kW)                                              | 23.5 hp (17.2 kW)                                              |
| Displacement                  | 44.3 cu. in. (726 cc)                                          | 44.3 cu. in. (726 cc)                                          |
| Fuel Capacity                 | 7.8 gal. (29.5 L)                                              | 7.8 gal. (29.5 L)                                              |
| Air Filter                    | Dual-Stage Canister                                            | Dual-Stage Canister                                            |
| <b>ELECTRICAL</b>             |                                                                |                                                                |
| Charging System               | 15 amp                                                         | 15 amp                                                         |
| Clutch                        | 125 lbf. (556 N)                                               | 125 lbf. (556 N)                                               |
| <b>DECK</b>                   |                                                                |                                                                |
| Mower Deck                    | AirFX Cutting System                                           | AirFX Cutting System                                           |
| Leading Edge                  | Adjustable, Front Lip Standard                                 | Adjustable, Front Lip Standard                                 |
| Width                         | 52.0 in. (1320 mm)                                             | 61.0 in. (1549 mm)                                             |
| Adjustable Anti-Scalp Rollers | 4                                                              | 6                                                              |
| Cutting Height                | 1.5-4.9 in. (38-124 mm)                                        | 1.5-4.9 in. (38-124 mm)                                        |
| Blade Tip Speed               | 18,142 fpm @ 3550 Engine rpm                                   | 18,809 fpm @ 3550 Engine rpm                                   |
| Discharge Chute               | Flexible Molded Polymer                                        | Flexible Molded Polymer                                        |
| <b>FRAME</b>                  |                                                                |                                                                |
| Front and Rear                | 1.5- x 2.5-inch Steel Tubing;<br>Welded Steel Reinforced Frame | 1.5- x 2.5-inch Steel Tubing;<br>Welded Steel Reinforced Frame |
| Machine Length                | 80.0 in. (2032 mm)                                             | 81.9 in. (2080 mm)                                             |
| Machine Weight (wet)          | 995 lb. (451 kg)                                               | 1043 lb. (473 kg)                                              |
| <b>TRANSMISSION</b>           |                                                                |                                                                |
| Type                          | HG ZT-3800 Hydrostatic Transaxles                              | HG ZT-3800 Hydrostatic Transaxles                              |
| Pump Displacement             | 0.7 cu. in. (12 cc)                                            | 0.7 cu. in. (12 cc)                                            |
| Oil Capacity                  | 1.0 gal. (4.0 qt.)                                             | 1.0 gal. (4.0 qt.)                                             |
| Forward Speed                 | 11.0 mph (17.7 km/hr.)                                         | 11.0 mph (17.7 km/hr.)                                         |
| Reverse Speed                 | 3.5 mph (5.6 km/hr.)                                           | 3.5 mph (5.6 km/hr.)                                           |
| <b>WHEELS</b>                 |                                                                |                                                                |
| Drive Wheel Size              | 24 x 10.5-12                                                   | 24 x 10.5-12                                                   |
| Front Caster Wheel Size       | 13 x 6.5-6                                                     | 13 x 6.5-6                                                     |
| Caster Arm Attachment         | Welded to Frame                                                | Welded to Frame                                                |
| <b>SEAT</b>                   |                                                                |                                                                |
| Description                   | High Back, Full Mechanical Suspension Seat                     | High Back, Full Mechanical Suspension Seat                     |
| Fore-Aft Adjustment           | Seat Slide Lever                                               | Seat Slide Lever                                               |
| <b>WARRANTY</b>               | 3-year/2,000-hour Limited Warranty                             |                                                                |